



## ADAPTER CARDS

# InfiniHost® III Ex

## Dual-Port InfiniBand adapter Cards with PCI Express x8

InfiniHost III Ex dual-port 4X InfiniBand adapter cards connect to the host system through a PCI Express x8 interface. Single data rate (SDR) InfiniHost III Ex cards support dual 10Gb/s InfiniBand connections while double data rate (DDR) versions support dual 20Gb/s InfiniBand connections. InfiniHost III Ex HCA cards deliver the most cost effective 10 or 20Gb/s solution available and feature remote direct memory access (RDMA), hardware transport, and advanced per queue pair (QP) QoS services.

All InfiniHost III Ex cards can be directly inserted into PCI Express x8 or wider slots of standard servers, blade servers, storage and communications platforms to enable InfiniBand fabrics. All adapter cards utilize 4X MicroGigaCN InfiniBand compliant connectors for copper cables. This copper connector provides the lowest cost 10 or 20Gb/s connection available. In addition, a plug-gable media adapter module can be used for fiber connections up to 300m.

### Feature Highlights

The MHEA28-1TC and MHGA28-1TC use 128MB or 256MB (-2TC) of local HCA attached SDRAM memory to store connection information directly on the adapter card.


Enabled by the high-bandwidth and low-latency capability of PCI Express, the MHEA28-XTC and MHGA28-XTC cards feature MemFree technology. This removes the requirement for local memory on the PCI Express adapter card itself, and instead, uses system memory to store connection information—resulting in lower power, lower adapter card cost, and smaller physical size.

InfiniHost III Ex HCA cards feature a full hardware implementation of the InfiniBand architecture memory protection and translation tables, as well as hardware transport. This drastically reduces processing overhead and allows the host CPU to spend its cycles on processing applications rather than network transport tasks.


Configuration and management of the adapter card can be handled through the PCI Express interface or in-band through the InfiniBand fabric.

### Software Support

All InfiniHost III Ex low profile adapter cards include verbs interface and device drivers for both Windows and Linux operating systems. In addition, the cards include internal Subnet Management Agent (SMA) and General Service Agents, eliminating the requirement for an external management agent CPU. The adapter are fully compatible with the open source OpenFabrics software suite. In addition to Linux and Windows, industry support for virtually all other operating systems is available including HP-UX, AIX, Solaris, and VxWorks.



**MHEA28-XTC** – Dual 10Gb/s InfiniBand  
MemFree w/ PCI Express x8



**MHEA28-1TC** – Dual 10Gb/s InfiniBand  
128MB local SDRAM w/ PCI Express x8

## BENEFITS

- Industry-standard technology
- Unified computing, storage and management
- High-bandwidth, low-latency
- Performance roadmap to 120Gb/s
- Highly-efficient clustering
- Ultimate reliability and scalability
- Multi-platform support
- Congestion management and QoS
- Virtualized I/O fabric
- World-class price/performance

## KEY FEATURES

- Dual 10Gb/s (MHEA28-XTC and MHEA28-1TC) or 20Gb/s (MHGA28-XTC and MHGA28-1TC) 4X InfiniBand Ports
- Integrated Serializer/Deserializer (SerDes) interfaces
- InfiniRISC™ embedded RISC processors
- PCI Express revision 1.0a compatible card
- PCI Express x8 (20 + 20Gb/s full duplex) interface
- IBTA version 1.2 compatible
- Copper InfiniBand connectors (MicroGigaCN) with media detect circuit for optional fiber media adapter
- ROHS-R5 Compliant

### SOFTWARE SUPPORT

- Linux and Windows drivers
- InfiniBand Compatible Verbs API
- Linux management and applications package available
- Various upper layer protocols

**KEY APPLICATIONS**

- Virtualized data centers that require a high-bandwidth, low-latency interconnect for server and storage grids
- High-performance parallelized computing leveraging Message Passing Interface (MPI) based applications such as molecular modeling, oil and gas exploration, car crash simulations, etc.
- Clustered database applications, parallel RDBMS queries, high-throughput data warehousing
- Performance storage applications such as backup, restore, mirroring, etc.
- High-bandwidth streaming content such as video-on-demand and HDTV
- Electronic Design Automation (EDA)
- Networking, Telecom and Industrial data acquisition.

**CHARACTERISTICS**

- Low Profile PCI Express card
- Requires 4X InfiniBand copper cable(s) (not included)
- Link status indication LED
- Serial EEPROM for Vital Product Data (VPD)
- Regulatory compliance testing
- ISO 9002 qualified manufacturing
- OEM labeling options



**HCA Card Family**

InfiniHost III Ex HCA Cards	InfiniBand Ports	Local Memory	Power (Typical)
MHEA28-1TC	Dual 10Gb/s	128MB	9.2W
MHEA28-2TC	Dual 10Gb/s	256MB	9.2W
MHGA28-1TC	Dual 20Gb/s	128MB	10W
MHGA28-2TC	Dual 20Gb/s	256MB	10W
MHEA28-XTC	Dual 10Gb/s	MemFree	7.8W
MHGA28-XTC	Dual 20Gb/s	MemFree	10.3W



350 Oakmead Parkway, Suite 100, Sunnyvale, CA 94085  
 Tel: 408-970-3400 • Fax: 408-970-3403  
[www.mellanox.com](http://www.mellanox.com)

© Copyright 2009. Mellanox Technologies. All rights reserved.  
 Mellanox, ConnectX, InfiniBlast, InfiniBridge, InfiniHost, InfiniRISC, InfiniScale, and InfiniPCI are registered trademarks of Mellanox Technologies, Ltd. Virtual Protocol Interconnect and BridgeX are trademarks of Mellanox Technologies, Ltd. All other trademarks are property of their respective owners.