

Tandberg Data LTO Half Height Drive

Leading Performance and Capacity

Tandberg Data LTO HH tape drives offer the best performance, reliability and value for small and medium-sized business users.

LTO technology makes it easy for users to standardize on a tape technology that meets today's data capacity requirements and can cope with future demands. LTO Ultrium is the industry standard and market leader. The six-generation roadmap ensures that data written today can be restored in later years.

The Tandberg Data family of LTO tape drives is the first choice for data protection for many small and medium-sized businesses with midrange and network storage environments. Tandberg Data LTO HH tape drives are available with a range of capacities, from 400GB*, 800GB*, 1.6TB* or 3TB*.

Tandberg Data LTO HH tape drives offer industry leading performance up to 1TB/hr* (280MB/sec* or 16.8GB/min*), reducing backup and restore times to a minimum. Tandberg Data provides a range of LTO HH models including internal, external and rackmount configurations, with either SCSI or SAS connectivity.

Tandberg Data LTO HH drives incorporate dynamic variable tape speed matching, allowing drives to constantly adapt speed to match the host/server data rate. This virtually eliminates "backhitching" or "shoe-shining," improving media life and reliability of backup and restore operations while reducing wear and tear on the tape drive. The advance air cooling design combined with low power consumption reduces IT costs and your carbon footprint.

The Tandberg Data LTO-5 HH drive includes a partitioning feature, which allows the tape drive to operate just like a large hard disk. The partitioning feature will greatly simplify archiving and should be of great interest to the video and broadcasting market.

Tandberg Data's extensive product testing program ensures that LTO drives are fully compatible with a wide range of servers, operating systems and backup software. Protect your business data for tomorrow with a Tandberg Data solution today.



Key Benefits

- High Capacity**
 Up to 3TB* of data on a single cartridge
- Leading Performance**
 Up to 1TB/hr* reducing backup and restore times
- Lower Storage Costs**
 LTO offers the lowest storage cost of any medium
- Archiving**
 LTO provides safe and secure storage of data for up to 30 years
- Reliability**
 MTBF of 250,000 hrs at 100% duty cycle
- Security**
 Protect your data with AES 256-bit Encryption (LTO-4 and 5 only)
- Minimize Downtime**
 3-year warranty and 3-years Advanced Replacement Service**

* Assumes a 2:1 compression ratio
 ** Availability dependent on location



Choose between 4 generations of LTO Half-Height drives for high capacity backup and archiving, with backward compatibility and the lowest power consumption in the industry.

Specifications

	Tandberg Data LTO-2 HH	Tandberg Data LTO-3 HH	Tandberg Data LTO-4 HH	Tandberg Data LTO-5 HH
Capacity (native/compr.)	200GB / 400GB*	400GB / 800GB*	800GB / 1.6TB*	1.5TB / 3.0TB*
Transfer Rate (native/compr.)	24MB/s / 48MB/s*	60MB/s / 120MB/s*	80MB/s / 160MB/s*	140MB/s / 280MB/s*
Dynamic Speed Matching	0–24MB/s / 0–40MB/s*	20–60MB/s / 40–120MB/s*	33–80MB/s / 66–160MB/s*	47–140MB/s / 94–280MB/s*
Memory Buffer Size	64MB	128MB	128MB	256MB
Data Access Speed	64 sec.	70 sec.	70 sec.	70 sec.
Interface Type	Ultra 160 SCSI Wide, Serial Attached SCSI 3Gbps	Ultra 320 SCSI Wide, Serial Attached SCSI 3Gbps	Ultra 320 SCSI Wide, Serial Attached SCSI 3Gbps, 4Gb Fibre Channel	Serial Attached SCSI 6Gbps
Interface Connector SCSI	68-pin HD (internal) 68-pin HD (external)	68-pin HD (internal) 68-pin HD (external)	68-pin HD (internal) 68-pin HD (external)	N/A
Interface Connector SAS	SFF8482 (internal)	SFF8482 (internal)	SFF8482 (internal) SFF8088 (external)	SFF8482 (internal) SFF8088 (external)
Data Compression (Enhanced version of ALDC)	LTO-DC	LTO-DC	LTO-DC	LTO-DC
Recording Format	LTO Ultrium 2, LTO Ultrium 1	LTO Ultrium 3, LTO Ultrium 2, LTO Ultrium 1 (read only)	LTO Ultrium 4, LTO Ultrium 3, LTO Ultrium 2 (read only)	LTO Ultrium 5, LTO Ultrium 4, LTO Ultrium 3 (read only)
Reliability				
MTBF Hours (100% duty cycle)	250,000 hours	250,000 hours	250,000 hours	250,000 hours
Head Life	60,000 tape running hours	60,000 tape running hours	60,000 tape running hours	60,000 tape running hours
Hard Error Rate	1 x 10⁽⁻¹⁷⁾ bits	1 x 10⁽⁻¹⁷⁾ bits	1 x 10⁽⁻¹⁷⁾ bits	1 x 10⁽⁻¹⁷⁾ bits
Environmental Specifications				
Temperature (Operating)	10C to 40C (50F to 95F)	10C to 40C (50F to 95F)	10C to 40C (50F to 95F)	10C to 40C (50F to 95F)
Temperature (Non-operating)	-40C to 66C (-40F to 151F)	-40C to 66C (-40F to 151F)	-40C to 66C (-40F to 151F)	-40C to 66C (-40F to 151F)
Relative Humidity (Operating)	20 to 80% (non-condensing)	20 to 80% (non-condensing)	20 to 80% (non-condensing)	20 to 80% (non-condensing)
Relative Humidity (Non-operating)	10% to 95% (non-condensing)	10% to 95% (non-condensing)	10% to 95% (non-condensing)	10% to 95% (non-condensing)
Power Requirements				
Idle	13 W	13 W	13 W	6.9 W
Typical	20 W	20 W	20 W	20 W
Maximum	33 W	33 W	33 W	33 W
Power Supply/ Required (int)	5V DC, 2.5A, 12V, 0.7A	5V DC, 2.5A, 12V, 0.7A	5V DC, 2.5A, 12V, 0.7A	5V DC, 2.5A, 12V, 0.7A
Certification	CSA Certification to C22.2, No. 60950 (cCSAus), TUV EN60950 (IEC 60950), CE Declaration of Conformity, FCC 47 CFR Parts 15, NOM, VCCI, C-TICK, RRL, BSMI, GOSH CB Certificate and Report (IEC 60950)			
Warranty	3-years Warranty and Advanced Replacement Service**			

* Assumes a 2:1 compression ratio
** Availability dependent on location

About Tandberg Data

Tandberg Data is a leading global supplier of data protection solutions. Tandberg Data offers a wide selection of secondary storage solutions, ranging from disk-based solutions, such as the RDX® QuikStor™ and the Tandberg Data DPS Series, to automated tape solutions like the StorageLoader and StorageLibrary Series. Tandberg Data also offers tape drives, based on the DAT, LTO™, SLR™ and VXA® tape technology platforms, and media. Tandberg Data solutions are supported by robust, easy-to-use software. All solutions are supported through a worldwide service and support network, recognized globally for its outstanding levels of service. Tandberg Data solutions are designed to meet the growing storage requirements of small and medium-sized organizations with scalability, reliability, and backward compatibility features that ensure cost-effective operation and long-term investment protection.

DS-LTOHH_US_2010A

Tandberg Data Corporation
2108 55th Street
Boulder, CO 80301
USA
Tel: 303.442.4333
Fax: 303.417.7170

Tandberg Data GmbH
Feldstrasse 81
44141 Dortmund
Germany
Tel: +49 (0) 231 5436 - 0
Fax: +49 (0) 231 5436 - 111

Tandberg Data (Asia) Pte. Ltd
7 Tai Seng Drive
#02-00
Singapore 535218
Tel: +65 6593 4700
Fax: +65 6281 7358

Tandberg Data (Japan) Inc.
Eitaibashi Eco-Piazza Bldg., 8th floor
29-13, Shinkawa 1-chome,
Chuo-ku, Tokyo 104-033, Japan
Tel: +81 355 662 871
Fax: +81 355 662 875

Specifications subject to change without notice. Tandberg Data StorageLoader, StorageLibrary, SecureService, DPS Series, RDX QuikStor and SLR are trademarks of Tandberg Data. RDX is a registered trademark of ProStor Systems. LTO is a trademark of HP, IBM and Quantum. All other trademarks are the property of their respective owners.
©2010 TANDBERG DATA. All rights reserved.