

## Tandberg StorageLibrary T24

*High-Performance Data Protection for SMBs*

The StorageLibrary T24 combines high capacity and performance in a small 2U form factor. The StorageLibrary T24 offers up to 38.4TB\* of compressed data storage and is designed to address the ever-growing demands for affordable, reliable, secure and high performance data storage.

Tandberg Data understands that your data needs change over time, so we've created the StorageLibrary T24 to easily scale from a 1x12 autoloader to a 2x24 library. The StorageLibrary T24 supports up to two half height LTO drives or one full height LTO drive and is available with LVD SCSI, SAS and Native Fibre Channel connectivity.

The StorageLibrary T24 is easy to install and easy to use and is fully certified by all leading backup software. The Performance on Demand (POD) feature allows you add additional drives or upgrade to the next LTO generation, increasing your library's performance and capacity. Adding, replacing or upgrading the tape drives is easy and can even be performed when the library is still in its rack—saving you time and money.

The Web browser-based remote management interface allows you to monitor, control, configure and diagnose problems from anywhere in the world. The StorageLibrary T24 supports system monitoring via SNMP. It also supports SMTP, and will immediately send an e-mail on any error.

The StorageLibrary T24 supports the latest security and data protection features, such as Encryption and WORM (Write Once Read Many) to assist you with meeting today's data storage and archiving regulatory requirements.

The StorageLibrary T24 provides outstanding value for IT managers that require a easy to use, scalable, flexible, reliable and future proof backup and data protection solution.



### Key Benefits

#### Capacity on Demand

Start with 12 slots, expand to 24 slots, increasing capacity from 19.2TB to 38.4TB\*

#### Performance on Demand

Add additional drives or upgrade and increase your library's performance and capacity

#### Blazing Transfer Rates

Performing faster backups saves time, energy and money, up to 1.7TB/hr (compressed)

#### Reliability

Tandberg Data's award-winning patented robotics is built on its 25-year legacy of superior engineering, quality and reliability

#### Industry-Leading Features

Includes a rack kit, Ethernet with remote management and a bar code reader.



The StorageLibrary T24 is well-suited to address the ever-growing demands for affordable, reliable, high-performance data protection of SMBs.

**Specifications**

|                                   | StorageLibrary T24 (12 slots)   | StorageLibrary T24 (24 slots)    |
|-----------------------------------|---|----------------------------------|
| Number of Drives (Half height)    | 1-2   | 1-2                              |
| Number of Drives (Full height)    | 1   | 1                                |
| Number of Cartridges              | 12  | 24                               |
| Capacity (Compressed)             | LTO-3 9.6TB   | 19.2TB                           |
|                                   | LTO-4 19.2TB  | 38.4TB                           |
| Max Performance (Compressed)      | LTO-3 HH 432GB/hr   | 432GB/hr                         |
|                                   | LTO-3 FH 576GB/hr   | 576GB/hr                         |
|                                   | LTO-4 HH 1728GB/hr  | 1728GB/hr                        |
|                                   | LTO-4 FH 864GB/hr   | 864GB/hr                         |
| Interface                         | LTO-3 HH Ultra SCSI LVD / Native FC / SAS   | Ultra SCSI LVD / Native FC / SAS |
| (SCSI LVD = 68pin HD)             | LTO-3 FH Ultra SCSI LVD / Native FC   | Ultra SCSI LVD / Native FC       |
| (Native FC = LC port)             | LTO-4 HH Ultra SCSI LVD / SAS   | Ultra SCSI LVD / SAS             |
| (SAS = SFF-8088)                  | LTO-4 FH Ultra SCSI LVD / Native FC   | Ultra SCSI LVD / Native FC       |
| Remote Management (Web)           | Standard  | Standard                         |
| Barcode Scanner                   | Standard  | Standard                         |
| Rackmount-option                  | Standard  | Standard                         |
| WORM (Write Once Read Many)       | Standard  | Standard                         |
| Encryption                        | LTO-4 only  | LTO-4 only                       |
| Cartridge Loading                 | 1 Magazine  | 2 Magazines                      |
| Temperature (Operating)           | 10C to 40C (50F to 104F)  | 10C to 40C (50F to 104F)         |
| Temperature (Non-operating)       | -30C to 60C (-22F to 140F)  | -30C to 60C (-22F to 140F)       |
| Relative Humidity (Operating)     | 20 to 80% (non-condensing)  | 20 to 80% (non-condensing)       |
| Relative Humidity (Non-operating) | 10 to 90% (non-condensing)  | 10 to 90% (non-condensing)       |
| Power                             | Power 100 to 240 VAC, 50 to 60 Hz, Library (maximum operating): 65 W RMS, Auto switching power supply |                                  |
| Warranty Reliability              | MTBF - 250 000 hours  | MTBF - 250 000 hours             |
| Software Compatibility            | The StorageLibrary T24 is compatible with all major backup applications and operating systems         |                                  |
| Agency Certification              | CE, FCC, TUV/GS, ICES VCCI, BSMI, CISPR 22, C-tick, UL, C-UL, CB, GOST and EN 55022 Class A           |                                  |

\*Assumes a 2:1 compression ratio

| Form Factors | Dimensions                       | Shipping Dimensions |
|--------------|----------------------------------|---------------------|
| Height       | 3.45 in. (8.75cm) 2U rack height | 11.1 in. (28.19cm)  |
| Width        | 17.57 in. (44.63cm)              | 22.5 in. (57.15cm)  |
| Length       | 30.53 in. (77.54cm)              | 35.95 in. (91.31cm) |
| Weight       | 43 lbs. (19.5kg)                 | 61 lbs. (27.7kg)    |

**About Tandberg Data**

Tandberg Data is a leading global supplier of backup and archiving technologies. Tandberg Data offers a complete range of tape libraries, tape autoloaders and tape drives (based on the LTO™, SLR™, VXA® tape technology platforms), storage software, data media and disk-based storage such as the RDX® QuikStor™. These solutions are marketed exclusively through a channel of qualified resellers and distributors. These solutions are underpinned by OEM agreements with major server manufacturers including IBM, Hitachi, Fujitsu, Fujitsu-Siemens, Apple and Dell and supported by all major operating systems and storage software applications to operate in heterogeneous network environments. All solutions are designed to meet the growing storage requirements of small and medium-sized organisations with scalability, reliability and backward compatibility features that ensure cost effective operation and long-term investment protection.

Tandberg Data ASA  
Økernveien 94  
N-0579 Oslo  
Norway  
Tel: +47 (0) 2218 9090  
Fax: +47 (0) 2218 9550

Tandberg Data GmbH  
Feldstrasse 81  
44141 Dortmund  
Germany  
Tel: +49 (0) 231 5436 - 0  
Fax: +49 (0) 231 5436 - 111

Tandberg Data Limited  
Bloxham Mill Business Centre  
Barford Road, Bloxham  
Banbury, England, OX15 4FF  
Tel: +44 (0) 845 070 6916  
Fax: +44 (0) 1295 722 109

Tandberg Data S.A.S.  
Multi Management Service  
55 rue de l'Université  
75007 Paris, France  
Téléphone: 00 800 826 323 74  
Télécopie: +33 (0)1 34 65 02 89

Tandberg Data Corporation  
2108 55th Street  
Boulder, CO 80301  
USA  
Tel: 303.442.4333  
Fax: 303.417.7170

Tandberg Data (Asia) Pte Ltd  
20 Bendemeer Road  
#04-05 Cyberhub  
Singapore 339914  
Tel: +65 (0) 6396 0786  
Fax: +65 (0) 6396 0787

In addition to the offices above TANDBERG DATA ASA has branch offices in the United Kingdom, France, Italy, India, China (PRC), Thailand and Brazil. TANDBERG DATA ASA is a publicly held company based in Oslo, Norway and is traded on the Oslo Stock Exchange (ticker=TAD). Specifications subject to change without notice. RDX QuikStor, BAKStor, and SLR are trademarks of Tandberg Data ASA. RDX is a registered trademark of ProStor Systems. LTO is a trademark of HP, IBM and Quantum. All other trademarks are the property of their respective owners. ©2009 TANDBERG DATA. All rights reserved.